



KOJI IZABRATI?



BETON	+	+	+
MERMER	+	+	+
CIGLA	+	+	+
GIPS	o	+	o
KERAMIKA	+	+	+
DRVO	+	+	+
IVERICA	o	+	+
BLAŽUJKA	+	+	+
PLUTA	+	+	+
ALUMINIJUM	+	+	o
GVOŽĐE	+	+	o
MESING	+	+	o
OBOJENI LIM	+	+	+
STAKLO	+	+	+
PLEKSIGLAS	+	+	+
OGLEDALA	+	+	o
XPS (Stirodur)	+	+	+
EPS (Stiropor)	+	+	+
PVC	+	+	+
ABS	+	+	+
POLIESTER	+	+	+
POLIKARBONAT	o	+	+
za spoljašnju i unutrašnju upotrebu	+	+	+
nanosi se na vlažne površine	+	+	+
vodootpornost	+	+	+
lako se boji	+	+	o
trenutno početno prijanjanje - 2 s	+	/	/
konačna čvrstina 430 kg/10 cm ²	+	/	/
mogućnost primene pod vodom	+	/	/
providna masa	/	/	+
elastična masa	o	+	o
otpornost na buđ	o	+	o
otpornost na snažnije potrese i vibracije	o	+	o
temperaturna postojanost: -40 °C do +90 °C	+	+	+
bez silikona i izocianata	+	+	+
POWER-BOOST tehnologija	+	+	+
20 godina garancije	+	+	+
sertifikat Ecode EC1 Plus	+	+	+



20
year
warranty



SOLVENT FREE

o - veoma dobro prijanjanje, + - odlično prijanjanje